

SPECIALIZED DESANDERS INC.™
Multiphase Desanding Services



www.desanders.com

SDI MODEL 62016-4880 S3FA



MAWP: 4,880 psi [33,647 kPa]
ANSI: 2500
MDMT: -20°F [-29°C]
DESIGNATED SERVICE: AB Sour
WEIGHT (EMPTY): 7,256 kg
LENGTH: 4.8 m
LIQUID VOLUME: 394 L
SAND CAPACITY: 647 kg
FITTING CONFIGURATION: 3" flanged

For more information, please visit www.desanders.com or contact one of the following SDI sales representatives:

SPECIALIZED DESANDERS INC.™
Multiphase Desanding Services



BRETT MCNAUGHTON
Sales & Marketing Manager

bmcnaughton@desanders.com 3355-114 Ave SE, Suite 111
C: 587.679.1760 Calgary, Alberta
P: 403.233.2040 T2Z 0K7

desanders.com

SPECIALIZED DESANDERS INC.™
Multiphase Desanding Services



DAN BLUNT
Account Manager

dblunt@desanders.com 3355-114 Ave SE, Suite 111
C: 403.801.8707 Calgary, Alberta
P: 403.233.2040 T2Z 0K7

desanders.com

SPECIALIZED DESANDERS INC.™
Multiphase Desanding Services



WILL RANSON
Account Manager

wranson@desanders.com 3355-114 Ave SE, Suite 111
C: 403.797.1760 Calgary, Alberta
P: 403.233.2040 T2Z 0K7

desanders.com

Gells, foam and emulsions have been known to cause sand carry over. Desander Performance below 29 API not proven.
Recommended Sand Laden velocities: below 15m/s is considered optimal, above 30m/s increases risk of erosive failure
Recommended Clean Fluid velocities: between 30m/s is considered optimal, above 45m/s increases risk of erosive failure