

# SPECIALIZED DESANDERS INC.™



*The Most Trusted Sand Solution*

## SDI MODEL 21615-1480



MAWP: 1,480 psi [10,200 kPa]

ANSI: 600

MDMT: -50°F [-44°C]

DESIGNATED SERVICE: Nace

WEIGHT (EMPTY): 2,515 kg

LENGTH: 6.8 m

LIQUID VOLUME: 362 L

SAND CAPACITY: 643 kg

FITTING CONFIGURATION: 4" flanged

*Gels, foam and emulsions have been known to cause sand carry over. Desander performance below 29 API not proven.  
Recommended Sand Laden velocities: below 15m/s is considered optimal, above 30m/s increases risk of erosive failure.  
Recommended Clean Fluid velocities: between 30m/s is considered optimal, above 45m/s increases risk of erosive failure.*

For more information, please visit [www.desanders.com](http://www.desanders.com) or contact one of the following SDI representatives:

### SPECIALIZED DESANDERS INC.™



**BRETT McNAUGHTON**  
Sales & Marketing Manager

[bmcnaughton@desanders.com](mailto:bmcnaughton@desanders.com)  
C: 587.679.1760  
P: 403.233.2040

3355-114 Ave SE, Suite 111  
Calgary, Alberta  
T2Z 0K7

• [desanders.com](http://desanders.com)

### SPECIALIZED DESANDERS INC.™



**CYNDY TREICHEL**  
Sales & Marketing Coordinator

[ctreichel@desanders.com](mailto:ctreichel@desanders.com)  
C: 403.701.5175  
P: 403.233.2040

111-3355 114 Ave SE  
Calgary, Alberta  
T2Z 0K7

• [desanders.com](http://desanders.com)