

SPECIALIZED DESANDERS INC.™



The Most Trusted Sand Solution

SDI MODEL 2810-1440



MAWP: 1,440 psi [9,928 kPa]
ANSI: 600
MDMT: -20°F [-28.9°C]
DESIGNATED SERVICE: Sweet
WEIGHT (EMPTY): 1,155 kg
LENGTH: 4.1 m
LIQUID VOLUME: 37 L
SAND CAPACITY: 60 kg
FITTING CONFIGURATION: 2" flanged

Gels, foam and emulsions have been known to cause sand carry over. Desander performance below 29 API not proven. Recommended Sand Laden velocities: below 15m/s is considered optimal, above 30m/s increases risk of erosive failure. Recommended Clean Fluid velocities: between 30m/s is considered optimal, above 45m/s increases risk of erosive failure.

For more information, please visit www.desanders.com or contact one of the following SDI representatives:

SPECIALIZED DESANDERS INC.™



BRETT McNAUGHTON
Sales & Marketing Manager

bmcnaughton@desanders.com
C: 587.679.1760
P: 403.233.2040

3355-114 Ave SE, Suite 111
Calgary, Alberta
T2Z 0K7

desanders.com

SPECIALIZED DESANDERS INC.™



CYNDY TREICHEL
Sales & Marketing Coordinator

ctreichel@desanders.com
C: 403.701.5175
P: 403.233.2040

111-3355 114 Ave SE
Calgary, Alberta
T2Z 0K7

desanders.com