

SPECIALIZED DESANDERS INC.™



The Most Trusted Sand Solution

SDI MODEL 41215-2900



MAWP: 2,900 psi [19,995 kPa]
ANSI: 1500
MDMT: -50°F [-44°C]
DESIGNATED SERVICE: AB sour
WEIGHT (EMPTY): 1,990 kg
LENGTH: 6.8 m
LIQUID VOLUME: 147 L
SAND CAPACITY: 260 kg
FITTING CONFIGURATION: 3" flanged

*Gells, foam and emulsions have been known to cause sand carry over. Desander performance below 29 API not proven.
Recommended Sand Laden velocities: below 15m/s is considered optimal, above 30m/s increases risk of erosive failure.
Recommended Clean Fluid velocities: between 30m/s is considered optimal, above 45m/s increases risk of erosive failure.*

For more information, please visit www.desanders.com or contact one of the following SDI representatives:

SPECIALIZED DESANDERS INC.™



BRETT M^oNAUGHTON
Sales & Marketing Manager

bmcnaughton@desanders.com
C: 587.679.1760
P: 403.233.2040

3355-114 Ave SE, Suite 111
Calgary, Alberta
T2Z 0K7

• desanders.com

SPECIALIZED DESANDERS INC.™



CYNDY TREICHEL
Sales & Marketing Coordinator

ctreichel@desanders.com
C: 403.701.5175
P: 403.233.2040

111-3355 114 Ave SE
Calgary, Alberta
T2Z 0K7

• desanders.com